

■ FEATURES

- 85°C
- Standard low leakage current series.

■ SPECIFICATIONS

Item	Performance											
	RLA											
Life	At 85°C 2000 Hrs											
Operating Temperature	-40°C ~ +85°C											
Capacitance Tolerance	± 20% (120Hz, 20°C)											
Leakage Current (at 20°C)	I = 0.002CV or 0.4 (μA) whichever is greater (after 2 minutes) Where, C = rated capacitance in μ F. V=rated DC working voltage in V.											
Dissipaton Factor Tan δ at 120 Hz, 20°C	Rated Voltage Tan δ(max)	6.3	10	16	25	35	50	63	100			
		0.24	0.21	0.16	0.14	0.12	0.10	0.09	0.08			
	When the capacitance exceed 1000 μ F 0.02 shall be added every 1000 μ F.											
Low Temperature Characteristics (at 120Hz)	Impedance ratio shall not exceed the values given in the table below											
	Rated Voltage		6.3	10	16	25	35	50	63	100		
	Impedance Ratio	Z(-25°C)/Z(+20°C)	5	4	2	2	2	2	2	2		
		Z(-40°C)/Z(+20°C)	10	8	6	4	4	3	3	3		
Load Life Test	Test Time	2000 Hrs					Shelf Life Test	Test Time	1000 Hrs			
	Capacitance Change	≤ ± 20%						Capacitance Change	≤ ± 20%			
	Dissipation Factor	Less than 200% of specified value						Dissipation Factor	Less than 200% of specified value			
	Leakage Current	Within specified value						Leakage Current	Within specified value			
	Specification shall be satisfied when the capacitors are restored to 20°C after rated voltage applied for 2000 hrs. at 85°C.					Specification shall be satisfied when the capacitors are restored to 20°C after exposing them for 1000 hrs at 85°C without voltage applied.						
Ripple Current & Frequency Multipliers	Freq. (Hz) Cap. (μF)	60(50)	120	500	1K	10K up	Riple Current & Temperature Multipliers		Temperature (°C) Multipliers	Under 50	70	85
	Under 100	0.70	1.00	1.35	1.55	2.00				1.75	1.58	1.00
	220 to 1000	0.83	1.00	1.23	1.32	1.50						
	2200 up above	0.90	1.00	1.12	1.10	1.15						
	Standards	Satisfies Characteristic W of JIS C 5141										

■ DIMENSIONS AND PERMISSIBLE RIPPLE CURRENT

Dimension: D×L(mm)

Ripple Current: mA/RMS at 120Hz 85°C

VDC		6.3V(0J)		10V(1A)		16V(1C)		25V(1E)		35V(1V)		50V(1H)		63V(1J)		100V(2A)	
μ F	Code	DXL	mA	DXL	mA	DXL	mA	DXL	mA	DXL	mA	DXL	mA	DXL	mA	DXL	mA
0.1	0R1											5 x 11	1.3			5 x 11	2.6
0.22	R22											5 x 11	2.9			5 x 11	5.8
0.33	R33											5 x 11	4.4			5 x 11	8.8
0.47	R47											5 x 11	7			5 x 11	12
1	010											5 x 11	13			5 x 11	22
2.2	2R2											5 x 11	29			5 x 11	33
3.3	3R3											5 x 11	35			5 x 11	40
4.7	4R7							5 x 11	31	5 x 11	40	5 x 11	42	5 x 11	45	5 x 11	48
10	100					5 x 11	44	5 x 11	54	5 x 11	58	5 x 11	65	5 x 11	70	6.3 x 11	80
22	220			5 x 11	59	5 x 11	75	5 x 11	80	5 x 11	87	5 x 11	95	6.3 x 11	115	8 x 11.5	135
33	330	5 x 11	55	5 x 11	84	5 x 11	90	5 x 11	97	5 x 11	105	6.3 x 11	125	6.3 x 11	140	10 x 12.5	195
47	470	5 x 11	79	5 x 11	100	5 x 11	110	5 x 11	115	6.3 x 11	145	6.3 x 11	150	8 x 11.5	190	10 x 16	255
100	101	5 x 11	130	5 x 11	145	6.3 x 11	180	6.3 x 11	190	8 x 11.5	240	8 x 11.5	255	10 x 12.5	320	13 x 20	450
220	221	6.3 x 11	230	6.3 x 11	250	8 x 11.5	300	8 x 11.5	320	10 x 12.5	420	10 x 16	490	10 x 20	565	16 x 25	810
330	331	6.3 x 11	280	8 x 11.5	350	8 x 11.5	370	10 x 12.5	470	10 x 16	570	10 x 20	650	13 x 20	765	16 x 25	990
470	471	8 x 11.5	380	8 x 11.5	415	10 x 12.5	520	10 x 16	620	10 x 20	740	13 x 20	860	13 x 25	990	16 x 31.5	1250
1000	102	10 x 12.5	650	10 x 16	790	10 x 20	910	13 x 20	1090	13 x 25	1300	16 x 25	1530	16 x 31.5	1700		
2200	222	13 x 20	1150	13 x 20	1240	13 x 25	1420	16 x 25	1660	16 x 31.5	1890	18 x 35.5	2160				
3300	332	13 x 20	1380	13 x 25	1590	16 x 25	1840	16 x 31.5	2070	18 x 35.5	2340						
4700	472	16 x 25	1880	16 x 25	1980	16 x 31.5	2260	18 x 35.5	2520	18 x 40	2690						

■ DIMENSIONS AND PERMISSIBLE RIPPLE CURRENT


Dimension: D×L(mm)

Ripple Current: mA/rms at 100K Hz 105°C


VDC Code μF	6.3V(0J)					10V(1A)					16V(1C)				
	DxL	Impedance		Ripple current		DxL	Impedance		Ripple current		DxL	Impedance		Ripple current	
		(Ω) Max @ 100KHz		(mA rms) @ 105°C			(Ω) Max @ 100KHz		(mA rms) @ 105°C			(Ω) Max @ 100KHz		(mA rms) @ 105°C	
		20°C	-10°C	120Hz	100KHz		20°C	-10°C	120Hz	100KHz		20°C	-10°C	120Hz	100KHz
33											5 x 11	1.30	3.90	108	154
39											5 x 11	1.30	3.90	108	154
47						5 x 11	2.10	5.50	78	111	6.3 x 11	0.60	1.80	182	260
56						5 x 11	1.90	4.80	85	121	6.3 x 11	0.60	1.80	182	260
68						5 x 11	1.30	3.90	108	154	6.3 x 11	0.60	1.80	182	260
100	5 x 11	1.30	3.90	108	154	6.3 x 11	0.60	1.80	182	260	6.3 x 11	0.60	1.80	182	260
220	6.3 x 11	0.60	1.80	182	260	8 x 11.5	0.33	0.99	280	400	8 x 11.5	0.33	0.99	320	400
330	8 x 11.5	0.33	0.88	280	400	8 x 11.5	0.33	0.99	280	400	10 x 12.5	0.25	0.75	360	510
390	8 x 11.5	0.33	0.88	320	400	10 x 12.5	0.27	0.70	410	510	10 x 16	0.19	0.57	510	635
470	10 x 12.5	0.25	0.75	410	510	10 x 12.5	0.25	0.75	410	510	10 x 16	0.19	0.57	510	635
560	10 x 12.5	0.25	0.75	410	510	10 x 16	0.19	0.57	510	635	10 x 20	0.14	0.42	775	860
680	10 x 16	0.19	0.57	510	635	10 x 16	0.19	0.57	510	635	10 x 20	0.14	0.42	775	860
1000	10 x 20	0.14	0.42	690	860	10 x 20	0.14	0.37	690	860	12.5 x 20	0.085	0.26	1000	1250
1200	10 x 20	0.14	0.42	775	860	10 x 25	0.12	0.30	930	1030	12.5 x 20	0.085	0.26	1125	1250
2200	12.5 x 20	0.085	0.26	1125	1250	12.5 x 25	0.070	0.21	1200	1355	12.5 x 25	0.070	0.21	1200	1355
3300	12.5 x 25	0.070	0.21	1200	1355	12.5 x 25	0.070	0.21	1200	1355	16 x 31.5	0.048	0.14	1830	2030
4700	16 x 25	0.060	0.18	1595	1770	16 x 31.5	0.048	0.14	1830	2030	16 x 35.5	0.044	0.13	2065	2295

■ LEAD SPACING AND DIAMETER SPECIFICATIONS

D	5	6.3	8	10	13	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
d	0.5		0.6			0.8	
α	1.0			1.5			
β	0.5						



■ HOW TO MAKE A PART NUMBER



1. Series: RLA

2. Capacitance: Rated capacitance in μ F is represented by a three digit number. The first two digits are the significant figures of the nominal capacitance and the third digit indicates the number of zeros following these figures. The decimal point is represented by the capital letter R. Please refer to the following example.

μ F	0.1	0.47	1	4.7	10	47	100	470	1000	4700	10000
Part Number	0R1	R47	010	4R7	100	470	101	471	102	472	103

3. Tolerance: (20% IS Typical)

Code	K	M	T	W
Tolerance	$\pm 10\%$	$\pm 20\%$	$\pm 50\% / -10\%$	$\pm 100\% / -10\%$

4. Rated Voltage: Voltage in volts (V) is represented by a two digit code showing the rated working voltage indicated as follows:

Voltage (WV)	6.3	10	16	25	35	40	50	63	80	100	160	200	250	350	400	450
Code	0J	1A	1C	1E	1V	1G	1H	1J	1K	2A	2C	2D	2E	2V	2G	2W

5. Lead Forming & Package

Code	Lead Description	Packaging
BC	Bending Cut	Bulk Packing
BK	Straight Lead	Bulk Packing
CC	Lead Cutting	Bulk Packing
FC	Lead Forming & Cutting	Bulk Packing
SD	Cathode Lead Beading	Bulk Packing
SA	Straight Lead	Tape & Ammo
TA	Lead Forming	Tape & Ammo
SR	Straight Lead	Tape & Reel
TR	Lead Forming	Tape & Reel

6. Can Size

Diameter (mm)x10 & Length (mm)x10. Can Size 063110, represents 6.3mm diameter by 11mm length.

7. Sleeve Type* = (Omit) PVC Sleeve

P = PET Sleeve

*Note: All standard RFE Aluminum Electrolytic Capacitors are Lead (Pb) free and RoHS compliant. PET sleeve is available for those companies that also require PVC free product.

LEADED TAPING & PACKAGING SPECIFICATIONS Taping Specification for Radial Lead Type

Fig. 1




Fig. 2




Fig. 3






Fig. 4



Packing	TA, TR (Fig. 1)								SA, SR (Fig. 2, 3, 4)											
L	L ≤ 7mm					L ≥ 7mm			L ≤ 7mm					L ≥ 7mm						
Symbol D	3	4	5	6.3	8	5	6.3	8	3	4	5	6.3	8	5	6.3	8	Tol.	10	13	Tol.
d	0.4	0.45	0.5	0.5	0.5	0.5	0.5	0.6	0.4	0.45	0.45	0.45	0.45	0.5	0.5	0.6	± 0.05	0.6	0.6	± 0.05
F	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	2.5	2.5	2.5	2.5	3.5	2.5	2.5	3.5	-0.2/+0.8	5.0	5.0	-0.2/+0.8
P	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	± 1.0	12.7	25.4	± 1.0
P0	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	± 0.2	12.7	12.7	± 0.30
P2	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	± 1.0	6.35	6.35	± 1.3
P1	3.85	3.85	3.85	3.85	3.85	3.85	3.85	3.85	5.1	5.1	5.1	5.1	4.6	5.1	5.1	4.6	± 0.5	3.85	3.85	± 0.7
H	17.5	17.5	17.5	17.5	17.5	18.5	18.5	20.0	17.5	17.5	17.5	17.5	17.5	18.5	18.5	18.5	± 0.75	18.5	18.5	± 0.75
H0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	--	--	--	--	--	--	--	--	± 0.5	--	--	± 0.5
W	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	± 0.5	18.0	18.0	± 0.5
W0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	12.0	Min	12.0	12.0	Min.
W1	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	± 0.5	9.0	9.0	± 0.5
W2	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	Max.	1.5	1.5	Max.
D0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	± 0.2	4.0	4.0	± 0.2
t	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	± 0.2	0.7	0.7	± 0.2
Δ H	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	± 1.0	0	0	± 1.0
ι	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	Max.	1.0	1.0	Max.
A	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	Max.	11	11	Max.
Fig. No.	1	1	1	1	1	1	1	1	2	2	2	3	3	2	3	3		3	3,4	

Ammo pack box.(SA,TA) Reel pack box.(SR,TR)
10 Boxes per carton



Packaging Quantity




D	3	4	5	6.3	8	10	13
TA, SA	3000	2000	2000	2000	1000	500	250
TR, SR	3000	1500	1200	1000	800	500	500

NOTES:

1. The above quantities are typical. Quantities may vary.
2. The component will be oriented on the tape so that the positive lead is leading or the negative lead is leading, depending on the customer's request

■ RADIAL FORMING

Lead Forming & Cutting Specifications for Radial Type (Unit: mm)

Forming Method	Code	Shape	Dimensions																																																																																
Forming Cut (4 ~ 8)	FC		<table><tr><th>D x L</th><th>d</th><th>F</th><th>F'</th><th>H</th></tr><tr><td>3 x 5</td><td>0.40</td><td>1.0</td><td>5.0</td><td>5.0</td></tr><tr><td>4 x 5</td><td>0.45</td><td>1.5</td><td>5.0</td><td>5.0</td></tr><tr><td>5 x 5</td><td>0.45</td><td>2.0</td><td>5.0</td><td>5.0</td></tr><tr><td>6.3 ~ 8 x 5</td><td>0.45</td><td>2.5</td><td>5.0</td><td>5.0</td></tr><tr><td>4 x 7</td><td>0.45</td><td>1.5</td><td>5.0</td><td>5.0</td></tr><tr><td>5 x 7 ~ 11</td><td>0.5</td><td>2.0</td><td>5.0</td><td>5.0</td></tr><tr><td>6 x 7 ~ 15</td><td>0.5</td><td>2.5</td><td>5.0</td><td>5.0</td></tr><tr><td>8 x 7 ~ 9</td><td>0.5</td><td>3.5</td><td>5.0</td><td>5.0</td></tr><tr><td>8 x 11.5 ~ 20</td><td>0.6</td><td>3.5</td><td>5.0</td><td>5.0</td></tr><tr><td>10</td><td>0.6</td><td>5.0</td><td>-</td><td>4.5</td></tr><tr><td>12.5</td><td>0.6</td><td>5.0</td><td>-</td><td>4.5</td></tr><tr><td>16</td><td>0.8</td><td>7.5</td><td>-</td><td>4.5</td></tr><tr><td>18</td><td>0.8</td><td>7.5</td><td>-</td><td>4.5</td></tr><tr><td>22</td><td>1.0</td><td>10.0</td><td>-</td><td>4.5</td></tr><tr><td>25</td><td>1.0</td><td>12.5</td><td>-</td><td>4.5</td></tr></table>	D x L	d	F	F'	H	3 x 5	0.40	1.0	5.0	5.0	4 x 5	0.45	1.5	5.0	5.0	5 x 5	0.45	2.0	5.0	5.0	6.3 ~ 8 x 5	0.45	2.5	5.0	5.0	4 x 7	0.45	1.5	5.0	5.0	5 x 7 ~ 11	0.5	2.0	5.0	5.0	6 x 7 ~ 15	0.5	2.5	5.0	5.0	8 x 7 ~ 9	0.5	3.5	5.0	5.0	8 x 11.5 ~ 20	0.6	3.5	5.0	5.0	10	0.6	5.0	-	4.5	12.5	0.6	5.0	-	4.5	16	0.8	7.5	-	4.5	18	0.8	7.5	-	4.5	22	1.0	10.0	-	4.5	25	1.0	12.5	-	4.5
			D x L	d	F	F'	H																																																																												
			3 x 5	0.40	1.0	5.0	5.0																																																																												
			4 x 5	0.45	1.5	5.0	5.0																																																																												
			5 x 5	0.45	2.0	5.0	5.0																																																																												
			6.3 ~ 8 x 5	0.45	2.5	5.0	5.0																																																																												
			4 x 7	0.45	1.5	5.0	5.0																																																																												
			5 x 7 ~ 11	0.5	2.0	5.0	5.0																																																																												
			6 x 7 ~ 15	0.5	2.5	5.0	5.0																																																																												
			8 x 7 ~ 9	0.5	3.5	5.0	5.0																																																																												
8 x 11.5 ~ 20	0.6	3.5	5.0	5.0																																																																															
10	0.6	5.0	-	4.5																																																																															
12.5	0.6	5.0	-	4.5																																																																															
16	0.8	7.5	-	4.5																																																																															
18	0.8	7.5	-	4.5																																																																															
22	1.0	10.0	-	4.5																																																																															
25	1.0	12.5	-	4.5																																																																															
Cut (3 ~ 25)	CC																																																																																		
Bending Cut (5 ~ 25)	BC		<table><tr><th>D x L</th><th>d</th><th>F±0.5</th></tr><tr><td>5 X 11</td><td>0.5</td><td>2.0</td></tr><tr><td>6.3 X 11 ~ 15</td><td>0.5</td><td>2.5</td></tr><tr><td>8 X 11.5 ~ 20</td><td>0.6</td><td>3.5</td></tr><tr><td>10</td><td>0.6</td><td>5.0</td></tr><tr><td>12.5</td><td>0.6</td><td>5.0</td></tr><tr><td>16</td><td>0.8</td><td>7.5</td></tr><tr><td>18</td><td>0.8</td><td>7.5</td></tr><tr><td>22</td><td>1.0</td><td>10.0</td></tr><tr><td>25</td><td>1.0</td><td>12.5</td></tr></table>	D x L	d	F±0.5	5 X 11	0.5	2.0	6.3 X 11 ~ 15	0.5	2.5	8 X 11.5 ~ 20	0.6	3.5	10	0.6	5.0	12.5	0.6	5.0	16	0.8	7.5	18	0.8	7.5	22	1.0	10.0	25	1.0	12.5																																																		
			D x L	d	F±0.5																																																																														
			5 X 11	0.5	2.0																																																																														
			6.3 X 11 ~ 15	0.5	2.5																																																																														
			8 X 11.5 ~ 20	0.6	3.5																																																																														
			10	0.6	5.0																																																																														
			12.5	0.6	5.0																																																																														
			16	0.8	7.5																																																																														
			18	0.8	7.5																																																																														
			22	1.0	10.0																																																																														
25	1.0	12.5																																																																																	
(10 ~ 25)	SD	